

A1
Amended

70 positioned on the motor shaft thereof, which engages a 23-toothed section gear 75 in an upward and downward direction, on one axis. The second motor 80 of the assembly 60 drives a 10-toothed fixed gear 85 positioned on the motor shaft thereof, which drives against an 82-toothed fixed gear 90 secured to a pivot shaft 100 with a snap ring 95. This preferably enables horizontal rotation of the housing 32 for 380-degrees on an axis that perpendicularly intersects the upward-downward axis of the gear 75 with respect to the pivot shaft 100. These motors 65, 80 are fixed with fasteners such as, screws, to a vertical pivot post 110 and a horizontal support assembly 120, respectively. The section gear is fixed with respect to the vertical pivot post 110, and the gear 90 is fixed with respect to the shaft 100.

IN THE CLAIMS:

Replace claim 1 with the following claim:

- A2
- B1
- 1.(AMENDED) A searchlight device comprising:
- a housing including a first end;
 - a window in the first end of said housing;
 - a lamp disposed within said housing so as to emit light through said window;
 - a shaft; and,
 - a positioning assembly secured within said housing, said positioning assembly including:
 - a first motor operable to rotate said housing in a first plane with respect to said shaft, and a
 - second motor operable to pivot said housing in a second plane with respect to said shaft.
-